

Board of Selectmen Meeting

Tuesday, September 24, 2019 7:00 PM 36 Bartlet Street, Andover, MA 01810 Selectmen's Conference Room

- I. Call to Order 7:00 P.M.
- II. Opening Ceremonies
 - A. Moment of Silence/Pledge of Allegiance
- III. Communications/Announcements/Liaison Reports
- IV. Citizens Petitions and Presentations
- V. Regular Business of the Board
 - A. <u>Human Trafficking Overview (20 minutes)</u>
 Chief of Police and Director of Public Health to provide an overview on human trafficking.
 - B. Columbia Safety Procedures (25 minutes)

Representatives of Columbia Gas to present an overview of safety procedures and protocols that will be followed during requested projects.

- VI. Public Hearings 8:00 P.M.
 - A. Columbia Gas (10 minutes)

Board to discuss and consider voting to approve a petition of Columbia Gas requesting permission to excavate for purposes of replacing and/or extending its mains according to submitted blueprints hereto annexed and made a part of this petition, and to make the necessary house connections along said extensions as follows: This project is to replace approximately 2300 feet of cast iron and bare steel gas main in Andover. The project scope includes Hidden Road (from South Main Street to Lantern Lane), Gardner Avenue and Forbes Street (from Hidden Road to Karlton Circle.)

B. Columbia Gas - (10 minutes)

Board to discuss and consider voting to approve a petition of Columbia Gas requesting permission to excavate for purposes of replacing and/or extending its mains according to submitted blueprints hereto annexed and made a part of this petition, and to make the necessary house connections along said extensions as follows: This project is to install approximately 40 feet of 4" PHIP gas main on Charlotte Drive from the end of the existing gas main towards 15 Charlotte Drive in order to install a new gas service to the requested meter location at 15 Charlotte Drive.

2019 SEP 20 P 2: 54

C. Columbia Gas - (10 minutes)

Board to discuss and consider voting to approve a petition of Columbia Gas requesting permission to excavate for purposes of replacing and/or extending its mains according to submitted blueprints hereto annexed and made a part of this petition, and to make the necessary house connections along said extensions as follows: To excavate approximately 2800 feet on High Plain Road from Beacon to 79 High Plain Road and 1,000 feet on Virginia Road and Shirley Road, for the purpose of replacing the Cast Iron/Bare Steel-low pressure gas main with Plastic-high pressure in order to retire the Andover low pressure system. All existing gas services within the project scope will be tied into the new Plastic-high pressure main. As part of the project, the low pressure gas regulator vault across from 185 Lowell Street and redundant gas main on Beacon Street (390' of 6" ST-LP) and Lowell Street (665' of 6" CI-LP) will be retied.

VII. Consent Agenda

A. <u>Appointments by the Town Manager</u> Board to vote that the following appointments by the Town Manager be approved:

Department	Name	Position	Rate/Term	Date of Hire	
Andover Green Advisory Board	Harry Vorhees	Member	Three years	9/25/19	
Commission on Disability	Faisal Bashir	Member	Three years	9/25/19	
Commission on Disability	S. David Kahan	Member	Three years	9/25/19	
Commission on Disability	Virginia McLeod	Member	Three years	9/25/19	
Commission on Disability	Mary Eileen Reilly	Member	Three years	9/25/19	
Town Clerk's Office	Stephanie Vaccaro	Customer Service Assistant	\$21.36/hour	9/30/19	
Community Services – Elder Services	Caren Connor	Office Assistant	\$21.36/hour	9/18/19	
Community Services – Elder Services	Patricia McCloskey	Office Assistant	\$21.36/hour	10/7/19	
Department of Public Works	Kiera Lawlor	Administrative Intern	\$14.00/hour	9/24/19	
Community Services -Recreation	Kathryn Allen	Kid Care	\$12.00/hour	9/16/19	
Community Services – Recreation	Madilyn Francis	Kid Care	\$12.25/hour	9/16/19	
Community Services – Recreation	Bryant Kroeger	Kid Care	\$11.25/hour	8/28/19	
Community Services – Recreation	Mafoudia Keita	Memorial Circle After School Program	\$11.25/hour	9/16/19	

Community Services –	Anthony	Memorial Circle	\$11.25/hour	9/16/19
Recreation	Mazzariello	After School		
		Program		
Community Services –	Erin Pero	Fitness Instructor	\$20.00/hour	9/23/19
Recreation				
Community Services	Rosie Scott	Seasonal	\$11.25/hour	9/10/19
-Youth Services				
Community Services	Timmy Kobelski	Seasonal	\$11.25/hour	9/14/19
-Youth Services				
Community Services –	Christina Reardon	Seasonal	\$12.00/hour	9/23/19
Youth Services				
Community Services –	Emma Accardi	Seasonal	\$12.00/hour	9/23/19
Youth Services				
Community Services –	Nina McKone	Seasonal	\$12.00/hour	9/23/19
Youth Services				
Community Services –	Benjamin	Seasonal	\$12.00/hour	9/23/19
Youth Services	Mergendahl			

VIII. Adjourn

If any member of the public wishing to attend this meeting seeks special accommodations in accordance with the Americans with Disabilities Act, please contact Kathryn Forina in the Town Manager's Office at 978-623-8215 or by email at kathryn.forina@andoverma.us

MEETINGS ARE TELEVISED ON COMCAST CHANNEL 22 AND VERIZON CHANNEL 45



TOWN OF ANDOVER

Town Clerk's Office

36 Bartlet Street Andover, MA 01810 978-623-8255 townclerk@andoverma.gov

NOTICE

You are hereby notified that the Public Hearing will be held by the Andover Select Board on Tuesday, September 10, 2019 has been continued to Tuesday, September 24, 2019 in the 3rd Floor Conference Room, Town Offices, 36 Bartlet Street, at 8 p.m.

Columbia Gas of Massachusetts requests permission to excavate for purposes of replacing and/or extending its gas mains, according to blueprints annexed and made a part of its petition, and to make the necessary house connections along said extensions, as follows:

This project is to replace approximately 2300 feet of cast iron and bare steel gas main in Andover. The project scope includes Hidden Road (from South Main Street to Lantern Lane), Gardner Avenue, and Forbes Street (from Hidden Road to Karlton Circle).

JO#: 17-0841883-00

Should you have any concerns about this proposal, please contact Veena Kothapalli at 978-314-8061 prior to the above-mentioned Select Board's hearing date. A representative of the company will be available at 6:45 P.M. on the above date to answer any other questions you may have relating to the proposed work.

Plan(s) of the proposed work can be found on the Town of Andover web site at www.andoverma.gov in the Open Meeting Calendar by searching under the public hearing date.

By order of the Select Board

Austr Link

Austin Simko Town Clerk

Plan No.: **17-0841883-00** Date: September 13, 2019



INSTALLATION ORDER NUMBER 17-0841883-00 ABANDONMENT ORDER NUMBER 17-0841884-00 PROJECT ID 17-48840 HIDDEN RD, ANDOVER

JOB TYPE: REPLACEMENT (557/558)

PROJECT INFORMATION

FIELD ENGINEER/TECHNICIAN:

K MURRAY

CONSTRUCTION FLL:

K WELLS / J ANGELARI

PERIVITS:

CITY PERMIT STATE PERMIT ENVIRONMENTAL PERMIT

TCC/LOA:

8400

ESSEX (009)

COUNTY:
TAX DISTRICT/TOWNSHIP ID:

0000401


MAP/GRID NUMBER: SYSTEM NUMBER(S):

24 HR. EMERGENCY LINE:

AND-063 80001012

COLUMBIA GAS OF MASSACHUSETTS 1-800-525-8222

VICINITY MAP



PROJECT DESCRIPTION

THIS PROJECT IS TO REPLACE APPROXIMATELY 2300' OF CAST IRON AND BARE STEEL GAS MAIN ON HIDDEN ROAD, GARDNER AVE, AND FORBES LANE IN ANDOVER. THIS PROJECT IS PLANNED DUE TO A MUNICIPAL PAVING PROJECT ON HIDDEN ROAD AND GARDNER AVE.

SHEET INDEX

DWG.	DESCRIPTION
T-1	TITLE SHEET
GN-1	GENERAL NOTES
ENV-1	ENVIRONMENTAL PLAN NARRATIVE
O-1	OVERVIEW SHEET
L-1 - L-2	LAYOUT PLANS
D-1	CONSTRUCTION DETAILS

PROJECT SUMMARY TABLE

PROPOSED INSTALLATION				PROPOSED ABANDONMENT				
LENGTH (FT)	SIZE (LENGTH (F		SIZE (IN)	TYPE	
1,600'	6"	,		790'	-,	8"	Cl	
730'	4"		PH		70'		6"	CI
					930'		4"	CI
					55'		8"	PL
					20'		6"	PL
					455'		6"	ST
2,330	TOTAL	. INSTALI	LATION (FEET)		2,320 TOTAL ABAND		ONMENT (FEET)	
PROPOSED GAS SERVICES								
		REPLA	ACEMENTS	Т	TE OVERS	TC	OTAL SERVICES	METER OUTS
ESTIMATED GAS SERVICES 10		10		12		10	7	







00/2 1/20 10

PROPOSED

REVISIONS						
0	7/5/19	INITIAL ISSUE - PERMIT COPY				
REV. #	DATE	DESCRIPTION				

DESIGNED BY	K MURRAY	7/3/19	978-802-5728
DRAWN BY	K MURRAY	7/3/19	978-802-5728
CHECK'D BY	Х	Х	Х
AS-BUILT BY	Х	Х	Х
	NAME	DATE	PHONE #

SITE NAM

INST# 17-0841883-00 ABAN# 17-0841884-00 PROJECT ID# 17-48840

HIDDEN RD, ANDOVER ANDOVER, ESSEX (009)

DRAWING TITLE:

TITLE SHEET

DRAWING NO:

T₋1

General Notes

- 1. The proposed gas main shown is approximate and is subject to change.
- 2. Property lines, structures, street lines, etc. were compiled using the NiSource GIS and are to be considered approximate.
- 3. Existing utilities, where shown, have been compiled from above ground evidence only and are to be considered approximate. NiSource does not guarantee the location of the underground utilities shown or that all existing utilities and/or subsurface structures are shown.
- 4. This project will adhere to all applicable federal, state or local permitting requirements for abandonment and installation of natural gas pipelines. All Federal, State, and Local codes and standards will be adhered including, but not limited to, the following: Code of Federal Regulations (CFR)
 - 49 CFR 192 Pipeline Safety Regulations
 - 29 CFR 1910 Occupational Safety and Health Administration (OSHA)

American Society of Mechanical Engineers (ASME)

ASME B31.8 Gas Transmission and Distribution Piping Systems

- 5. All NiSource design codes and standards will be adhered to as applicable. These standards include but are not limited to the following (note state-specific designations where applicable):
 - GS 1100.010(IN, KY, MA, MD, OH, PA, VA) Locating Gas Facilities
 - GS 1100.040(MA and VA only) Damage Prevention When Using Conventional Excavation Technologies
 - GS 1100.050(IN, OH, VA) Damage Prevention Using Trenchless Technology
 - GS 1170.010(IN) Gas Control Room Management
 - GS 1210.010(MA) Nondestructive Testing And Visual Inspection
 - GS 1300.010 Fusion And Mechanical Joining
 - GS 1301.010 Plastic Pipe Fusion And Mechanical Joining Qualification Of Personnel
 - GS 1302.010(VA) Butt Fusion Joining
 - GS 1304.010 Electrofusion Joining
 - GS 1320.010 Mechanical Coupling Connections
 - GS 1323.010 Flange Connections
 - GS 1400.010 Corrosion Control General
 - GS 1410.010(VA) Metallic Pipeline Exposures
 - GS 1420.035 Coating Repair Methods For Mill Applied Coatings
 - GS 1420.040 Coating Methods For Girth Welds, Fittings, Risers & Other Below Grade Appurtenances
 - GS 1420.410 Corrosion Control Inspection Of Steel Pipe Coating
 - GS 1420.510 Installation Of Galvanic Anodes
 - GS 1420.520 Installation Of Test Stations
 - GS 1430.320 Ultrasonic Thickness Gauge
 - GS 1500.010(MA, OH) Pressure Testing
 - GS 1670.020(IN, KY, MA, MD) Odor Level Monitoring GS 1670.040 Pipeline Conditioning New Pipelines
 - GS 1680.010 Tie-Ins And Tapping Pressurized Pipelines
 - GS 1680.020 Plastic To Steel Transition Connections
 - GS 1680.040 Squeeze Off Procedure For Plastic Pipe
 - GS 1680.050 Squeeze Off Guidelines For Steel Pipe
 - GS 1690.010 Purging
 - GS 1708.020(IN, KY, MA, MD, PA) Leakage Surveys
 - GS 1740.010(MA, OH, PA, VA) Abandonment Of Facilities
 - GS 1740.012(MA, PA) Abandoning Facilities Service Tee Removal
 - GS 1742.010(VA) Discontinuing Gas Service
 - GS 1754.010(KY, OH) Operation And Maintenance Of Pressure Gauges
 - GS 1770.010 Prevention Of Accidental Ignition
 - GS 1782.010(MA) Protecting Cast Iron Pipelines
 - GS 3000.020(VA) Inspection Of Materials GS 3000.900 Work Site Restoration
 - GS 3010.030 Bends And Elbows
 - GS 3010.050(IN, MA) Installation Of Pipe In A Ditch
 - GS 3010.060(IN) Installation Of Plastic Pipe
 - GS 3010.080(MA, OH, VA) Underground Clearance
 - GS 3010.090(IN, MA, PA, VA) Cover
 - GS 3010.100(VA) Transmission Lines And Distribution Mains Trenchless Technology
 - GS 3010.102(VA) Directional Boring
 - GS 3010.210(MA only) Use Of End Caps On Steel Pipe
 - GS 3020.030 Service Line Connections To Main Piping
 - HSE 4100.010 Hazardous Atmosphere Considerations HSE 4100.020 Work Zone Traffic Protection
 - HSE 4100.040 Excavation (Trenching) Safety
 - HSE 4120.010 Welding And Cutting
 - HSE 4200.020 Protective Footwear
 - HSE 4200.030 Eye And Face Protection
 - HSE 4200.040 Hand Protection
 - HSE 4200.050 Head Protection
 - HSE 4440.030(KY, MA, MD, OH, PA, VA) Spoil Handling During Excavations
 - ON 18-09 Additional Requirements For Tie-Ins Involving Low Pressure Facilities
 - WM Columbia Gas Welding Manual

- 6. Prior to beginning any excavation on site, the person responsible for earth moving shall notify utility owners of their intent to excavate and to have the exact locations of the utility lines marked by contacting the one call center in their state subject to any applicable state advance notification requirements.
- 7. Proposed or completed gas facility installation location references may be indicated by a combination of the following codes:
 - F FRONT BK - BACK L - LEFT R - RIGHT B - BUILDING EDGE
 - **CLP CENTER OF PAVEMENT**
 - CLR CENTER OF RIGHT-OF-WAY **CEL - CENTER OF EASTBOUND LANE**
 - CWL CENTER OF WESTBOUND LANE
 - CNL CENTER OF NORTHBOUND LANE CSL - CENTER OF SOUTHBOUND LANE
- CU CURB
- D DRIVEWAY EDGE
- EP EDGE OF PAVEMENT
- ES EDGE OF SIDEWALK
- PL PROPERTY LINE

DRAWING LEGEND

Gas Main Syn	shology
Gas Main Syn	Existing Gas Main
	Existing Gas Main to Be Abandoned
	Proposed Gas Main
	Proposed Gas Main Uprate
Gas Main Mat	erial/Pressure Label References
CS Wall Wat	Coated Steel Gas Main
CI	Cast Iron Gas Main
BS	Bare Steel Gas Main
WI	Wrought Iron Gas Main
PH	High Density Polyethylene Gas Main
PM	Medium Density Polyethylene Gas Main
LP	Low Pressure
IP	Intermediate Pressure
MP	Medium Pressure
HP	High Pressure
Gas Main Inst	allation Method Label References
AT	Attached
BH	Bridge Hanger
BLGH	Building Hanger
DB	Directional Bore
IS	Inserted
OC	Open Cut
PB	Pneumatic Bore
PL	Plowed
RT	Roof Top
(E)	Existing
(P)	Proposed
— (W1)	Weld Location
T1	Cae Main Tie in Legation
— <u>(T1)</u>	Gas Main Tie-in Location
—(A1)	Gas Main Abandonment Location

Coo Ecollity Cym	phology
Gas Facility Sym	
⊗4"GV	Gas Valve (Gate - GV, Plug - PV, PE Ball - BP, ST Ball - BV)
⊗ 4"PV	Critical Gas Valve
	High Volume Tapping Tee
○ 2"SST	Pressure Control Fitting - ShortStopp Tee
	Pressure Control Fitting - Spherical Tee
○ 6"MF-BO	Pressure Control Fitting - Mueller Bottom-out
○ 6"MF-SO	Pressure Control Fitting - Mueller Side-out
○ 4"MF-FT	Pressure Control Fitting - Mueller Flange Tee
□ 4"SS	Pressure Control Fitting - ShortStopp
	Pressure Control Fitting - ShortStopp
×6x4 POLYTAP	5 11
	Transition
_	End Cap
Ð 4	Riser Reducer
EM	Electronic Marker
TWS	Flush-mounted Tracer Wire Station
<u> </u>	Post Pipeline Marker with Tracer Wire
MM	Gas Main Marker without Tracer Wire
(w)	Test Well
$\langle \overline{R} \rangle$	Regulator Station
R	Single Customer Regulator
$\langle M \rangle$	Meter
MR	Meter with Regulator
声	Test Point (Station)
T	Gas Service Tie-over
R	Gas Service Replacement
MMO	Meter Move Out
Swing Tie Symb	
①	Telephone Manhole
(D)	Drain Manhole
Ē	Electric Manhole
	Catch Basis
⑤	Sewer Manhole
⊗	Fire Hydrant
•	Utility Pole Property Marker
	·
C	Telephone Pedestal Television Pedestal
	I GIGVISIUIT F GUGSLAI

Unknown Manhole

Electric Pedestal

Water Box

Water Gate

Iron Pin

Light Pole





09/24/2049

PROPOSED

REVISIONS						
0	7/5/19	INITIAL ISSUE - PERMIT COPY				
REV. #	DATE	DESCRIPTION				

		NAME	DATE	PHONE #
	AS-BUILT BY	Х	Х	Х
ı	CHECK'D BY	X	Χ	Х
	DRAWN BY	K MURRAY	7/3/19	978-802-5728
	DESIGNED BY	K MURRAY	7/3/19	978-802-5728

SITE NAME:

INST# 17-0841883-00 ABAN# 17-0841884-00 PROJECT ID# 17-48840 HIDDEN RD, ANDOVER

ANDOVER, ESSEX (009)

DRAWING TITLE:

GENERAL NOTES

DRAWING NO:

GN-1

Environmental Plan Narrative

- 1. A Site-Specific Erosion Control plan is required for this project. This plan, with the project Environmental Compliance Plan (ECP), provide information regarding all environmental requirements.
- 2. The project ECP and the site-specific EC plan must be reviewed with environmental, construction and contractor personnel prior to the start of construction activities. This includes any tree clearing activities required prior to the start of pipeline construction.
- 3. All NiSource construction activities must be performed in accordance with the NiSource Environmental Construction Standards (ECS) and the project ECP.
- 4. All NiSource construction projects must have a clearly defined work area or limits of disturbance (LOD). The LOD includes the permitted project area and any additional work space needed for laydown yards, soil stockpiling areas, access routes, etc. Identify the LOD in the field with NRP or the Environmental Inspector before work starts and notify NRP of any additional work space that may be needed.

Description and Minimum Requirements for Erosion and Sediment Control Measures

The information provided below outlines the purpose of common EC measures and how and when they shall be applied to the site. Figures showing installation details are provided in the NiSource ECS manual. Requirements outlined in the site-specific EC plan must be implemented in addition to these minimum requirements.

Perimeter Barriers: Perimeter barriers, such as silt fence and compost filter sock may be installed along the outside of the project area or around sensitive areas to slow and filter sediment laden runoff before it leaves the work area.

These measures are required in the following areas:

- . When work is occurring adjacent to streams, wetlands or other sensitive areas.
- 2. Around HDD bore pits adjacent to streams, wetlands or other sensitive areas.
- 3. Around soil stockpiles that will remain uncovered for greater than one working day.
- 4. Where any work areas or excavations will remain disturbed (unstabilized) for longer than one working day.

Inlet Protection: Storm drain inlet protection, both curb and drop inlets, are required in active work areas where there is functioning storm sewer to slow and filter water draining into the system. In areas where the work area is adjacent to, or water from the site flows onto a paved roadway, inlet protection will be placed in all functioning outlets.

Check dams: Rock check dams may be installed in areas of concentrated flow in a ditch line to slow runoff and allow sediment to settle prior to discharge. Check dams may also be used as a break in a perimeter barriers where runoff is concentrated and perimeter barriers are insufficient to detain runoff. Check dams are required when working in ditch lines where work will remain active for more than 1 day and as a supplementary measure determined to be needed during construction.

Dewatering Devices: A filter bag, or other approved dewatering device, must be used during all dewatering activities to remove suspended sediment from the water prior to discharge into the environment. Dewatering devices must be used in areas including, but not limited, to trench or pit dewatering and treatment of excess HDD mud.

Construction Entrances: In cases where vehicular access from the work area occurs at a single point for multiple days, a rock construction entrance must be installed. A stabilized construction entrance may not be feasible during construction within or immediately adjacent to a roadway as the construction project moves linearly along the road. In these cases, care should be taken to minimize vehicular access and the roadway shall be regularly cleaned of tracked sediment throughout the work day. Alternatives to rock entrances include the placement of timber mats or similar non erodible materials. Use of these alternatives must be approved by the NRP group or environmental inspector.

Trench Plugs/Breakers: Trench breakers consist of sand or earth filled sacks placed at intervals along the pipeline trench. Trench breakers may be installed at intervals within the trench to reduce water velocity along the pipeline bedding that can result in erosion during construction and after backfilling. Trench plugs consist of clay, bentonite or other impermeable material and are required adjacent to stream and wetland crossings to ensure that the flow of water along the trench line does not impact the waterbody.

Temporary Stabilization: Temporary stabilization includes the placement of an annual or cover crop and a straw or other mulch covering to protect disturbed areas from precipitation. In certain cases where redisturbance will occur prior to a normal germination period, temporary stabilization with mulch or other covering may be completed without the application of seed.

Temporary stabilization will be completed on the following areas to reduce erosion from bare ground during rainfall events:

- 1. Any areas, including stockpiles or tie-in pits, which will remain open overnight without perimeter controls.
- 2. Any work area that will remain bare/disturbed longer than 7 days (4 in PA) without being actively worked within that time. Seeding must be completed within this time window.

Permanent Stabilization: Includes the placement of a permanent seed mix and a straw or other mulch covering to permanently stabilize the disturbed areas. Proper ground/ seed bed preparation (e.g. topsoiling, raking, decompaction) shall be completed as appropriate to the existing site area to provide a sufficient surface for seed germination.

Permanent seeding shall be completed immediately after work completion in all work areas without structural controls; regardless of whether the surrounding area is vegetated. Permanent seeding shall be applied within 7 days (4 days in PA) of work completion in areas all other areas; with the exception of work area protected by adequate structural controls where the surrounding area is an active construction site and was not vegetated prior to the start of work.

Erosion Control Blanket/Matting: Erosion control blanket is a straw matting that can be rolled out over a disturbed area and secured using pins or stakes. This blanket may be used on steeper sloped areas to hold seed and mulch in place. Erosion control blanket can also be useful in protecting the seed and holding moisture in dry, windy areas. Erosion control blanket must be used in restoration adjacent to streams or wetlands. It should also be used in areas with high erosion potential (e.g. steep slopes, embankments, ditch lines)

Maintenance: The job site shall be inspected by construction personnel at the end of each day to ensure that any controls are functioning and that the work area is sufficiently contained. Required maintenance of NiSource installed controls or corrective actions shall be performed immediately or within the time frames noted by an Environmental Inspector.

Measures previously installed by third parties shall be maintained by NiSource under the following circumstances:

- 1. The control is not properly functioning and is being used to contain sediment and prevent erosion immediately adjacent to NiSource work.
- 2. Damage to the control is the result of work performed by NiSource.

Projects within Third Party Construction Sites:

In situations where NiSource projects are being completed within a larger project or development area, NiSource is still responsible for ensuring our work is in compliance with all laws and regulations. This must be documented under one of the following scenarios:

- 1. Prior to the start of construction activities, a qualified NiSource representative will verify that all NiSource work activities will be covered under the third party's approved site plan and/or SWPPP and that the appropriate EC measures are installed and functioning. This review will be documented and retained in the project records.
- 2. If the EC measures required by the third party's approved site plan are not present or functioning, NiSource construction activities may commence under the following conditions:
 - a. All disturbed NiSource work areas are stabilized at the end of the work day.
 - b. Any NiSource work areas requiring disturbance over one working day (e.g. stockpiles, tie-in pits) will require perimeter controls or temporary mulching or covering on a daily basis.
 - c. The overall project SWPPP is present/available and all NiSource activities remain within compliance of all outlined requirements.
 - d. Any additional permits required for the NiSource work are obtained.
 - e. The third party permit holder is informed of the site deficiencies and NiSource's plan to complete the work.

Final stabilization measures shall be completed as described in the applicable Temporary or Permanent Stabilization sections above to match the adjacent conditions of the third party project.

In addition to the preceding methods, the following erosion control measures will be used on a daily basis regardless of whether the work area is inside third party controls:

- Perimeter barriers around bore pits at wetland/ stream bores
- Dewatering activities using a filter bag or other approved method
- Roadway cleaning daily for sediment tracked onto paved surfaces

Wetland and Stream Crossings, Sensitive Areas:


All wetlands, stream crossings and other sensitive areas (e.g. managed lands, parks, and endangered species habitat areas) must be marked in the field with caution flagging prior to the start of clearing activities and/or land disturbing activities.

Any requirements for construction within these areas will be outlined within the ECP and the attached permit documents. These permits must also be reviewed prior to the start of construction.

ENVIRONMENTAL EROSION AND SEDIMENT CONTROL SYMBOLOGY

ENVIRONMENTAL EROSION CONTROL BLOCKS (on Env-ErosionControl layer)

(on Env-StreamLine layer)



Temporary Stabilization

Permanent Stabilization

Erosion Control Matting

Construction Entrance

Filter Sock (12")

Filter Sock (18")

Filter Sock (24")

_____ TP ____

.~~~~~.

_____ LOD _____

Tree Protection (on Env-TreeProtection layer) Tree Line (on Env-TreeLine layer)

(on Env-TreeLine layer)
Limits of Disturbance
(on Env-DisturbanceLimit layer)

N'Source[®]



09/24/2049

PROPOSED

REVISIONS						
0	7/5/19	INITIAL ISSUE - PERMIT COPY				
REV. #	DATE	DESCRIPTION				

DESIGNED BY	K MURRAY	7/3/19	978-802-5728
DRAWN BY	K MURRAY	7/3/19	978-802-5728
CHECK'D BY	Х	Х	Х
AS-BUILT BY	Х	Х	Х
	NAME	DATE	PHONE #

SITE NAME:

INST# 17-0841883-00 ABAN# 17-0841884-00 PROJECT ID# 17-48840 HIDDEN RD, ANDOVER ANDOVER, ESSEX (009)


DRAWING TITLE:

ENVIRONMENTAL NARRATIVE

DRAWING NO:

ENV-1





MATERIAL INFORMATION

(TO BE COMPLETED DURING CONSTRUCTION)

FITTING INSTALLATION DATA										
FITTING	TYPE	SIZE (IN)	STORES ITEM NUMBER (PO NUMBER IF NON-STOCK)	MATERIAL (MDPE, HDPE, STEEL)	JOINT TYPE	MANUFACTURER	LOT NUMBER	LOCATION 1	LOCATION 2	COMMENTS

	VALVE INSTALLATION DATA											
VALVE	TYPE	SIZE (IN)	STORES ITEM NUMBER (PO NUMBER IF NON-STOCK)	MATERIAL (MDPE, HDPE, STEEL)	MANUFACTURER	CLOCKWISE TO CLOSE?	TURNS TO CLOSE	PRESSURE RATING	DEPTH TO NUT	LOCATION 1	LOCATION 2	COMMENTS
						Y or N						

PIPELINE INSTALLATION DATA										
PIPE SEGMENT	SIZE (IN)	MATERIAL (MDPE, HDPE, STEEL)	STORES ITEM NUMBER (PO NUMBER IF NON-STOCK)	MANUFACTURER	PIPE DATA PLASTIC - SDR/STRAIGHT OR COIL STEEL - WALL/GRADE/SEAM TYPE/COATING	LOCATION	COMMENTS			

FITTING LEGEND

CONTROLLABLE FITTINGS		
FITTING TYPE	LABEL	SYMBOL
BOTTOM OUT MUELLER FITTING	4" MF-BO	$\overline{\mathbf{z}}$
HIGH VOLUME TEE	4x2 HVT	0
SHORTSTOPP	4" SS	Ø
FULL ENCIRCLEMENT SHORTSTOPP	4" SS-FE	Ø
FULL ENCIRCLEMENT SHORTSTOPP TEE	4" SST-FE	0
SIDE OUT MUELLER FITTING	4" MF-SO	¤
SPHERICAL TEE	4" SPH	0
MUELLER STOPPER	4" MF-ST	Ø
SHORTSTOPP TEE	4" SST	0


NONCONTROLLABLE FITTINGS

FITTING TYPE	LABEL	SYMBOL
BLOW-DOWN	BLOW-DOWN	N/A ^
BLOW-OFF	BLOW-OFF	N/A ^
CHECK VALVE	4" CHECK VALVE	\otimes
COUPLING	4" COUPLING	1
ELL	4" 90° ELL/45° ELL	N/A*
END CAP	4" DE CAP	1
LAUNCHER-RECEIVER	LAUNCHER-RECEIVER	N/A ^
PUMPKIN	PUMPKIN	1
REDUCER	4x2 REDUCER	◀
RELIEF	RELIEF	N/A ^
SADDLE	8x4 BRANCH SADDLE	N/A*
TEE	4" INLINE TEE	N/A*
TRANSITION	4" TRANSITION	1
WELD INSULATOR	4" WELD INSULATOR	1
RISER	4" PMMP-R/CSMP-R	റ

^ - "FITTING" TO BE REPRESENTED WITH DETAILED SKETCH OF FACILITY
* - FITTING INDICATED BY CHANGE IN DIRECTION (ELBOW) OR
INTERSECTION OF FACILITIES (INLINE TEE, BRANCH SADDLE)







PROPOSED

REVISIONS									
0	7/5/19	INITIAL ISSUE - PERMIT COPY							
REV.#	DATE	DESCRIPTION							

ı		NAME	DATE	PHONE #
ı	AS-BUILT BY	Х	Х	Х
ı	CHECK'D BY	Х	Χ	Χ
ı	DRAWN BY	K MURRAY	7/3/19	978-802-5728
ı	DESIGNED BY	K MURRAY	7/3/19	978-802-5728

SITE NAME

INST# 17-0841883-00 ABAN# 17-0841884-00 PROJECT ID# 17-48840 HIDDEN RD, ANDOVER


ANDOVER, ESSEX (009)

MATERIAL INFORMATION

DRAWING NO:

DRAWING TITLE:

L-1 M



MATERIAL INFORMATION

(TO BE COMPLETED DURING CONSTRUCTION)

	FITTING INSTALLATION DATA											
FITTING	TYPE	SIZE (IN)	STORES ITEM NUMBER (PO NUMBER IF NON-STOCK)	MATERIAL (MDPE, HDPE, STEEL)	JOINT TYPE	MANUFACTURER	LOT NUMBER	LOCATION 1	LOCATION 2	COMMENTS		

	VALVE INSTALLATION DATA											
VALVE	TYPE	SIZE (IN)	STORES ITEM NUMBER (PO NUMBER IF NON-STOCK)	MATERIAL (MDPE, HDPE, STEEL)	MANUFACTURER	CLOCKWISE TO CLOSE?	TURNS TO CLOSE	PRESSURE RATING	DEPTH TO NUT	LOCATION 1	LOCATION 2	COMMENTS
						Y or N						

PIPELINE INSTALLATION DATA									
PIPE SEGMENT	SIZE (IN)	MATERIAL (MDPE, HDPE, STEEL)	STORES ITEM NUMBER (PO NUMBER IF NON-STOCK)	MANUFACTURER	PIPE DATA PLASTIC - SDR/STRAIGHT OR COIL STEEL - WALL/GRADE/SEAM TYPE/COATING	LOCATION	COMMENTS		

FITTING LEGEND

<u> </u>	LGLND	
CONTROLLABLE FITTINGS		
FITTING TYPE	LABEL	SYMBOL
BOTTOM OUT MUELLER FITTING	4" MF-BO	$\overline{\mathbf{z}}$
HIGH VOLUME TEE	4x2 HVT	0
SHORTSTOPP	4" SS	Ø
FULL ENCIRCLEMENT SHORTSTOPP	4" SS-FE	Ø
FULL ENCIRCLEMENT SHORTSTOPP TEE	4" SST-FE	0
SIDE OUT MUELLER FITTING	4" MF-SO	¤
SPHERICAL TEE	4" SPH	0
MUELLER STOPPER	4" MF-ST	¤
SHORTSTOPP TEE	4" SST	0

NONCONTROLLABLE FITTINGS

NONCONTROLLABLE FITTINGS		
FITTING TYPE	LABEL	SYMBOL
BLOW-DOWN	BLOW-DOWN	N/A^
BLOW-OFF	BLOW-OFF	N/A ^
CHECK VALVE	4" CHECK VALVE	\otimes
COUPLING	4" COUPLING	1
ELL	4" 90° ELL/45° ELL	N/A*
END CAP	4" DE CAP	1
LAUNCHER-RECEIVER	LAUNCHER-RECEIVER	N/A ^
PUMPKIN	PUMPKIN	1
REDUCER	4x2 REDUCER	◀
RELIEF	RELIEF	N/A ^
SADDLE	8x4 BRANCH SADDLE	N/A*
TEE	4" INLINE TEE	N/A*
TRANSITION	4" TRANSITION	1
WELD INSULATOR	4" WELD INSULATOR	1
RISER	4" PMMP-R/CSMP-R	Ð

^ - "FITTING" TO BE REPRESENTED WITH DETAILED SKETCH OF FACILITY
* - FITTING INDICATED BY CHANGE IN DIRECTION (ELBOW) OR
INTERSECTION OF FACILITIES (INLINE TEE, BRANCH SADDLE)







09/24/2049

PROPOSED

	REVISIONS						
ı							
ı							
ı							
ı							
ı							
	0	7/5/19	INITIAL ISSUE - PERMIT COPY				
	REV.#	DATE	DESCRIPTION				

ı	DESIGNED BY	K MURRAY	7/3/19	978-802-5728
ı	DRAWN BY	K MURRAY	7/3/19	978-802-5728
ı	CHECK'D BY	Х	Х	Х
ı	AS-BUILT BY	Х	Х	Х
ı		NAME	DATE	PHONE #

SITE NAME

INST# 17-0841883-00 ABAN# 17-0841884-00 PROJECT ID# 17-48840 HIDDEN RD, ANDOVER

ANDOVER, ESSEX (009)

DRAWING TITLE:

MATERIAL INFORMATION

DRAWING NO:

L-2 M

		C	ONSTRUC	TION DET	AILS			
								MSource*
								<u>M</u>
								Know what's below. Call before you dig.
								Can before you dig.
								PROPOSED
								REVISIONS
								0 7/5/19 INITIAL ISSUE - PERMIT COPY REV. # DATE DESCRIPTION
								DESIGNED BY K MURRAY 7/3/19 978-802-5728 DRAWN BY K MURRAY 7/3/19 978-802-5728 CHECK'D BY X X X AS-BUILT BY X X X NAME DATE PHONE #
								INST# 17-0841883-00 ABAN# 17-0841884-00
								PROJECT ID# 17-48840 HIDDEN RD, ANDOVER ANDOVER, ESSEX (009)
								CONSTRUCTION DETAILS
								DRAWING NO:
								D-1

Columbia Gas – Hidden Road Motion

I move that the Board approve, subject to the review and approval of the Andover Department of Public Works Engineering Division and Andover Fire Rescue, the petition of Columbia Gas requesting the permission to excavate for the purpose of replacing and/or extending its gas mains, according to blueprints provided in the petition, and to make necessary house connections along said extensions, on Hidden Road (from South Main Street to Lantern Lane), Gardner Avenue, and Forbes Street (from Hidden Road to Karlton Circle).

Moved by		
Seconded by		
Voted	to	



TOWN OF ANDOVER

Town Clerk's Office

36 Bartlet Street Andover, MA 01810 978-623-8255 townclerk@andoverma.gov

NOTICE

You are hereby notified that the Public Hearing held by the Andover Select Board on Tuesday, September 10, 2019 has been continued to Tuesday, September 24, 2019 in the 3rd Floor Conference Room, Town Offices, 36 Bartlet Street, at 8 p.m.

Columbia Gas of Massachusetts requests permission to excavate for the purpose of replacing and/or extending its gas mains, according to blueprints annexed and made a part of its petition, and to make the necessary house connections along said extensions, as follows:

This project is to install approximately 40 feet of 4" PHIP gas main on Charlotte Drive from the end of the existing gas main towards 15 Charlotte Drive. This project is part of Columbia Gas' "Growth" budget and is necessary to install a new gas service to the requested meter location at 15 Charlotte Drive.

JO#: 19-0844250-00

Should you have any concerns about this proposal, please contact Veena Kothapalli at 978-314-8061 prior to the above-mentioned Select Board's hearing date. A representative of the company will be available at 6:45 P.M. on the above date to answer any other questions you may have relating to the proposed work.

Plan(s) of the proposed work can be found on the Town of Andover website at www.andoverma.gov in the Open Meeting Calendar by searching under the public hearing date.

By order of the Select Board

lustu Lunk

Austin Simko Town Clerk

JO#: 19-0844250-00

Date: September 13, 2019



INSTALLATION ORDER NUMBER 19-0844250-00 PROJECT ID 19-61713 15 CHARLOTTE DR, ANDOVER

JOB TYPE: GROWTH (555)

PROJECT INFORMATION

FIELD ENGINEER/TECHNICIAN:

CONSTRUCTION FLL:

K WELLS / J ANGELARI

PERMITS:

CITY PERMIT

TCC/LOA:

8400

COUNTY:

ESSEX

TAX DISTRICT/TOWNSHIP ID:


MAP/GRID NUMBER:

SYSTEM NUMBER(S):

24 HR. EMERGENCY LINE:

COLUMBIA GAS OF MASSACHUSETTS 1-800-525-8222

VICINITY MAP



PROJECT DESCRIPTION

THIS PROJECT IS TO INSTALL 40' OF 4" PHIP MAIN ON CHARLOTTE DRIVE, ANDOVER. THE PROPOSED INSTALLATION IS REQUIRED IN ORDER TO INSTALL A NEW GAS SERVICE TO 15 CHARLOTTE DRIVE.

SHEET INDEX

DWG.	DESCRIPTION
T-1	TITLE SHEET
GN-1	GENERAL NOTES
ENV-1	ENVIRONMENTAL PLAN NARRATIVE
L-1	LAYOUT PLANS
D-1	CONSTRUCTION DETAILS

PROJECT SUMMARY TABLE

PRC	PROPOSED INSTALLATION					PROPOSED ABANDONMENT			
LENGTH (FT)	LENGTH (FT) SIZE (IN)		TYPE LENGTH (FT)		- T)	SIZE (IN)	TYPE		
40'	4"	4" HDPE		0'					
			-						
40	TOTAL I	INSTALLATION (FEET))	0		TOTAL ABANDO	ONMENT (FEET)		
	PROPOSED GAS SERVICES								
		REPLACEMENTS	T	IE OVERS	TO	TAL SERVICES	METER OUTS		
ESTIMATED GAS S	SERVICES	0		0		1	0		







09/24/2019

PROPOSED

	REVISIONS					
0	7/11/19	INITIAL / PERMIT ISSUE				
REV. #	DATE	DESCRIPTION				
	· ·					

DESIGNED BY	K MURRAY	6/17/19	978-802-5728
DRAWN BY	K MURRAY	6/17/19	978-802-5728
CHECK'D BY	X	Х	Х
AS-BUILT BY	Х	Х	Х
	NAME	DATE	PHONE #

SITE NAME:

INST# 19-0844250-00 ABAN# XX-XXXXXXXXXX PROJECT ID# 19-61713

15 CHARLOTTE DR, ANDOVER ANDOVER, ESSEX

DRAWING TITLE:

TITLE SHEET

DRAWING NO:

T₋1

General Notes

- 1. The proposed gas main shown is approximate and is subject to change.
- 2. Property lines, structures, street lines, etc. were compiled using the NiSource GIS and are to be considered approximate.
- 3. Existing utilities, where shown, have been compiled from above ground evidence only and are to be considered approximate. NiSource does not guarantee the location of the underground utilities shown or that all existing utilities and/or subsurface structures are shown.
- 4. This project will adhere to all applicable federal, state or local permitting requirements for abandonment and installation of natural gas pipelines. All Federal, State, and Local codes and standards will be adhered including, but not limited to, the following: Code of Federal Regulations (CFR)
 - 49 CFR 192 Pipeline Safety Regulations
 - 29 CFR 1910 Occupational Safety and Health Administration (OSHA)

American Society of Mechanical Engineers (ASME)

ASME B31.8 Gas Transmission and Distribution Piping Systems

- 5. All NiSource design codes and standards will be adhered to as applicable. These standards include but are not limited to the following (note state-specific designations where applicable):
 - GS 1100.010(IN, KY, MA, MD, OH, PA, VA) Locating Gas Facilities
 - GS 1100.040(MA and VA only) Damage Prevention When Using Conventional Excavation Technologies
 - GS 1100.050(IN, OH, VA) Damage Prevention Using Trenchless Technology
 - GS 1170.010(IN) Gas Control Room Management
 - GS 1210.010(MA) Nondestructive Testing And Visual Inspection
 - GS 1300.010 Fusion And Mechanical Joining
 - GS 1301.010 Plastic Pipe Fusion And Mechanical Joining Qualification Of Personnel
 - GS 1302.010(VA) Butt Fusion Joining
 - GS 1304.010 Electrofusion Joining
 - GS 1320.010 Mechanical Coupling Connections
 - GS 1323.010 Flange Connections
 - GS 1400.010 Corrosion Control General
 - GS 1410.010(VA) Metallic Pipeline Exposures
 - GS 1420.035 Coating Repair Methods For Mill Applied Coatings
 - GS 1420.040 Coating Methods For Girth Welds, Fittings, Risers & Other Below Grade Appurtenances
 - GS 1420.410 Corrosion Control Inspection Of Steel Pipe Coating
 - GS 1420.510 Installation Of Galvanic Anodes
 - GS 1420.520 Installation Of Test Stations
 - GS 1430.320 Ultrasonic Thickness Gauge
 - GS 1500.010(MA, OH) Pressure Testing
 - GS 1670.020(IN, KY, MA, MD) Odor Level Monitoring GS 1670.040 Pipeline Conditioning New Pipelines
 - GS 1680.010 Tie-Ins And Tapping Pressurized Pipelines
 - GS 1680.020 Plastic To Steel Transition Connections
 - GS 1680.040 Squeeze Off Procedure For Plastic Pipe
 - GS 1680.050 Squeeze Off Guidelines For Steel Pipe
 - GS 1690.010 Purging
 - GS 1708.020(IN, KY, MA, MD, PA) Leakage Surveys
 - GS 1740.010(MA, OH, PA, VA) Abandonment Of Facilities
 - GS 1740.012(MA, PA) Abandoning Facilities Service Tee Removal
 - GS 1742.010(VA) Discontinuing Gas Service
 - GS 1754.010(KY, OH) Operation And Maintenance Of Pressure Gauges
 - GS 1770.010 Prevention Of Accidental Ignition
 - GS 1782.010(MA) Protecting Cast Iron Pipelines
 - GS 3000.020(VA) Inspection Of Materials
 - GS 3000.900 Work Site Restoration
 - GS 3010.030 Bends And Elbows GS 3010.050(IN, MA) Installation Of Pipe In A Ditch
 - GS 3010.060(IN) Installation Of Plastic Pipe
 - GS 3010.080(MA, OH, VA) Underground Clearance
 - GS 3010.090(IN, MA, PA, VA) Cover
 - GS 3010.100(VA) Transmission Lines And Distribution Mains Trenchless Technology
 - GS 3010.102(VA) Directional Boring
 - GS 3010.210(MA only) Use Of End Caps On Steel Pipe GS 3020.030 Service Line Connections To Main Piping
 - HSE 4100.010 Hazardous Atmosphere Considerations
 - HSE 4100.020 Work Zone Traffic Protection HSE 4100.040 Excavation (Trenching) Safety
 - HSE 4120.010 Welding And Cutting
 - HSE 4200.020 Protective Footwear
 - HSE 4200.030 Eye And Face Protection
 - HSE 4200.040 Hand Protection
 - HSE 4200.050 Head Protection
 - HSE 4440.030(KY, MA, MD, OH, PA, VA) Spoil Handling During Excavations
 - ON 18-09 Additional Requirements For Tie-Ins Involving Low Pressure Facilities
 - WM Columbia Gas Welding Manual

- 6. Prior to beginning any excavation on site, the person responsible for earth moving shall notify utility owners of their intent to excavate and to have the exact locations of the utility lines marked by contacting the one call center in their state subject to any applicable state advance notification requirements.
- 7. Proposed or completed gas facility installation location references may be indicated by a combination of the following codes:

F - FRONT BK - BACK L - LEFT R - RIGHT B - BUILDING EDGE

CLP - CENTER OF PAVEMENT CLR - CENTER OF RIGHT-OF-WAY

CEL - CENTER OF EASTBOUND LANE CWL - CENTER OF WESTBOUND LANE

CNL - CENTER OF NORTHBOUND LANE CSL - CENTER OF SOUTHBOUND LANE

CU - CURB

D - DRIVEWAY EDGE

EP - EDGE OF PAVEMENT ES - EDGE OF SIDEWALK

PL - PROPERTY LINE

DRAWING LEGEND

Plowed

Roof Top

Existing

Proposed

Weld Location

Gas Main Tie-in Location

Gas Main Abandonment Location

Gas	Main Symbology	Gas Facility Syn	nbology
	Existing Gas Main	⊗4"GV	Gas Valve (Gate - GV, Plug - PV, PE Ball - BP, ST Ball - BV)
	— Existing Gas Main to Be Abandoned	⊗ 4"PV	Critical Gas Valve
	— — Proposed Gas Main	○ 2"HVTT	High Volume Tapping Tee
	— Proposed Gas Main Uprate	○ 2"SST	Pressure Control Fitting - ShortStopp Tee
Gas	Main Material/Pressure Label References	○ 4"SPH	Pressure Control Fitting - Spherical Tee
CS	Coated Steel Gas Main	○ 6"MF-BO	Pressure Control Fitting - Mueller Bottom-out
CI	Cast Iron Gas Main	○ 6"MF-SO	Pressure Control Fitting - Mueller Side-out
BS	Bare Steel Gas Main	○ 4"MF-FT	Pressure Control Fitting - Mueller Flange Tee
WI	Wrought Iron Gas Main	¤4"SS	Pressure Control Fitting - ShortStopp
PH	High Density Polyethylene Gas Main	¤4"MF	Pressure Control Fitting - ShortStopp
PM	Medium Density Polyethylene Gas Main	imes6x4 POLYTAP	Polytapp Side Saddle Fitting
LP	Low Pressure	I	Transition
ΙP	Intermediate Pressure	_	End Cap
MP	Medium Pressure	Ð	Riser
HP	High Pressure	◀	Reducer
	Main Installation Method Label References	EM	Electronic Marker
ΑT	Attached	TWS	Flush-mounted Tracer Wire Station
BH	Bridge Hanger	>	Post Pipeline Marker with Tracer Wire
BLG	H Building Hanger	ММ	Gas Main Marker without Tracer Wire
DB	Directional Bore	(w)	Test Well
IS	Inserted	(R)	Regulator Station
OC	Open Cut	R	Single Customer Regulator
PB	Pneumatic Bore	M	Meter

0 WI -50	3
○ 4"MF-FT	Pressure Control Fitting - Mueller Flange Tee
¤4"SS	Pressure Control Fitting - ShortStopp
	Pressure Control Fitting - ShortStopp
\times 6x4 POLYTAP	Polytapp Side Saddle Fitting
	Transition
_	End Cap
Ð	Riser
◄	Reducer
EM	Electronic Marker
TWS	Flush-mounted Tracer Wire Station
	Post Pipeline Marker with Tracer Wire
MM	Gas Main Marker without Tracer Wire
⟨w⟩	Test Well
$\langle \overline{R} \rangle$	Regulator Station
R	Single Customer Regulator
$\langle M \rangle$	Meter
(MR)	Meter with Regulator
<u> </u>	Test Point (Station)
<u> </u>	Gas Service Tie-over
R	Gas Service Replacement
MMO	Meter Move Out
Swing Tie Symb	
①	Telephone Manhole
(D)	Drain Manhole
Ē	Electric Manhole
	Catch Basis
<u>\$</u>	Sewer Manhole
፟	Fire Hydrant
\leftrightarrow	Utility Pole
•	Property Marker
T	Telephone Pedestal
C	Television Pedestal
()	Unknown Manhole
WB	Water Box
WB O WG O	Water Gate
O E	Electric Pedestal
⊩ P	
	Iron Pin
*	Light Pole







09/24/2019

PROPOSED

REVISIONS					
0	7/11/19	INITIAL / PERMIT ISSUE			
REV.#	DATE	DESCRIPTION			

ı		NAME	DATE	PHONE #
	AS-BUILT BY	X	X	Х
ı	CHECK'D BY	Х	X	Χ
ı	DRAWN BY	K MURRAY	6/17/19	978-802-5728
ı	DESIGNED BY	K MURRAY	6/17/19	978-802-5728

SITE NAME:

INST# 19-0844250-00 ABAN# XX-XXXXXXXXXXXX PROJECT ID# 19-61713 15 CHARLOTTE DR, ANDOVER

ANDOVER, ESSEX

DRAWING TITLE:

GENERAL NOTES

DRAWING NO:

GN-1

Environmental Plan Narrative

- 1. There is no Site-Specific Erosion Control plan requirement for this project. This plan narrative, with the project Environmental Compliance Plan (ECP), provide information regarding all environmental requirements. All NiSource construction activities must be performed in accordance with the NiSource Environmental Construction Standards (ECS) and the project ECP.
- 2. The project ECP must be reviewed with construction and contractor personnel prior to the start of construction activities. This includes any tree clearing activities required prior to the start of pipeline construction.
- 3. All NiSource construction projects must have a clearly defined work area or limits of disturbance (LOD). The LOD includes the permitted project area and any additional work space needed for laydown yards, soil stockpiling areas, access routes, etc. Notify NRP of any additional work space that may be needed outside of what is shown on this job order sketch.

Description and Minimum Requirements for Erosion and Sediment Control Measures

The information provided below outlines the purpose of common measures and how and when they shall be applied to the site. Figures showing installation details are provided in the NiSource ECS manual.

Perimeter Barriers: Perimeter barriers, such as silt fence and compost filter sock may be installed along the outside of the project area or around sensitive areas to slow and filter sediment laden runoff before it leaves the work area.

These measures are required in the following areas:

- When work is occurring adjacent to streams, wetlands or other sensitive areas.
- Around HDD bore pits adjacent to streams, wetlands or other sensitive areas.
- Around soil stockpiles that will remain uncovered for greater than one working day.
- Where any work areas or excavations will remain disturbed (unstabilized) for longer than one working day.

Inlet Protection: Storm drain inlet protection, both curb and drop inlets, are required in active work areas where there is functioning storm sewer to slow and filter water draining into the system. In areas where the work area is adjacent to, or water from the site flows onto a paved roadway, inlet protection will be placed in all functioning outlets.

Check dams: Rock check dams may be installed in areas of concentrated flow in a ditch line to slow runoff and allow sediment to settle prior to discharge. Check dams may also be used as a break in a perimeter barriers where runoff is concentrated and perimeter barriers are insufficient to detain runoff. Check dams are required when working in ditch lines where work will remain active for more than 1 day and as a supplementary measure determined to be needed during construction.

Dewatering Devices: A filter bag, or other approved dewatering device, must be used during all dewatering activities to remove suspended sediment from the water prior to discharge into the environment. Dewatering devices must be used in areas including, but not limited, to trench or pit dewatering and treatment of excess HDD mud.

Construction Entrances: In cases where vehicular access from the work area occurs at a single point for multiple days, a rock construction entrance must be installed. A stabilized construction entrance may not be feasible during construction within or immediately adjacent to a roadway as the construction project moves linearly along the road. In these cases, care should be taken to minimize vehicular access and the roadway shall be regularly cleaned of tracked sediment throughout the work day. Alternatives to rock entrances include the placement of timber mats or similar non erodible materials. Use of these alternatives must be approved by the NRP group or environmental inspector.

Trench Plugs/Breakers: Trench breakers consist of sand or earth filled sacks placed at intervals along the pipeline trench. Trench breakers may be installed at intervals within the trench to reduce water velocity along the pipeline bedding that can result in erosion during construction and after backfilling. Trench plugs consist of clay, bentonite or other impermeable material and are required adjacent to stream and wetland crossings to ensure that the flow of water along the trench line does not impact the waterbody.

Temporary Stabilization: Temporary stabilization includes the placement of an annual or cover crop and a straw or other mulch covering to protect disturbed areas from precipitation. In certain cases where redisturbance will occur prior to a normal germination period, temporary stabilization with mulch or other covering may be completed without the application of seed.

Temporary stabilization will be completed on the following areas to reduce erosion from bare ground during rainfall events:

- Any areas, including stockpiles or tie-in pits, which will remain open overnight without perimeter controls.
- 2. Any work area that will remain bare/disturbed longer than 7 days (4 in PA) without being actively worked within that time. Seeding must be completed within this time window.

Permanent Stabilization: Includes the placement of a permanent seed mix and a straw or other mulch covering to permanently stabilize the disturbed areas. Proper ground/ seed bed preparation (e.g. topsoiling, raking, decompaction) shall be completed as appropriate to the existing site area to provide a sufficient surface for seed germination.

Permanent seeding shall be completed immediately after work completion in all work areas without structural controls; regardless of whether the surrounding area is vegetated. Permanent seeding shall be applied within 7 days (4 days in PA) of work completion in areas all other areas; with the exception of work area protected by adequate structural controls where the surrounding area is an active construction site and was not vegetated prior to the start of work.

Erosion Control Blanket/Matting: Erosion control blanket is a straw matting that can be rolled out over a disturbed area and secured using pins or stakes. This blanket may be required on steeper sloped areas to hold seed and mulch in place. Erosion control blanket can also be useful in protecting the seed and holding moisture in dry, windy areas. Erosion control blanket must be used in restoration adjacent to streams or wetlands. It should also be used in areas with high erosion potential (e.g. steep slopes, embankments, ditch lines).

Maintenance: The job site shall be inspected by construction personnel at the end of each day to ensure that any controls are functioning and that the work area is sufficiently contained. Required maintenance of NiSource installed controls or corrective actions shall be performed immediately or within the time frames noted by an Environmental Inspector.

Measures previously installed by third parties shall be maintained by NiSource under the following circumstances:

- 1. The control is not properly functioning and is being used to contain sediment and prevent erosion immediately adjacent to NiSource work.
- 2. Damage to the control is the result of work performed by NiSource.

Projects Within Third Party Construction Sites:

In situations where NiSource projects are being completed within a larger project or development area, NiSource is still responsible for ensuring our work is in compliance with all laws and regulations. This must be documented under one of the following scenarios:

- Prior to the start of construction activities, a qualified NiSource representative will verify that all NiSource work activities will be covered under the third party's approved site plan and/or SWPPP and that the appropriate EC measures are installed and functioning. This review will be documented and retained in the project records.
- 2. If the EC measures required by the third party's approved site plan are not present or functioning, NiSource construction activities may commence under the following conditions:
 - a. All disturbed NiSource work areas are stabilized at the end of the work day.
 - b. Any NiSource work areas requiring disturbance over one working day (e.g. stockpiles, tie-in pits) will require perimeter controls or temporary mulching or covering on a daily basis.
 - The overall project SWPPP is present/available and all NiSource activities remain within compliance of all outlined
 - Any additional permits required for the NiSource work are obtained.
 - The third party permit holder is informed of the site deficiencies and NiSource's plan to complete the work.

Final stabilization measures shall be completed as described in the applicable Temporary or Permanent Stabilization sections above to match the adjacent conditions of the third party project.

In addition to the preceding methods, the following erosion control measures will be used on a daily basis regardless of whether the work area is inside third party controls:

- Perimeter barriers around bore pits at wetland/ stream bores
- Dewatering activities using a filter bag or other approved method
- Roadway cleaning daily for sediment tracked onto paved surfaces


Wetland and Stream Crossings, Sensitive Areas:

All wetlands, stream crossings and other sensitive areas (e.g. managed lands, parks, and endangered species habitat areas) must be marked in the field with caution flagging prior to the start of clearing activities and/or land disturbing activities.

Any requirements for construction within these areas will be outlined within the ECP and the attached permit documents. These permits must also be reviewed prior to the start of construction.


ENVIRONMENTAL EROSION AND SEDIMENT CONTROL SYMBOLOGY


ENVIRONMENTAL EROSION CONTROL BLOCKS (on Env-ErosionControl layer)











09/24/2019

PROPOSED

	REVISIONS									
Ш	0	7/11/19	INITIAL / PERMIT ISSUE							
	REV.#	DATE	DESCRIPTION							

	DESIGNED BY	K MURRAY	6/17/19	978-802-5728
ı	DRAWN BY	K MURRAY	6/17/19	978-802-5728
ı	CHECK'D BY	Х	Х	Х
ı	AS-BUILT BY	Х	Х	Х
1		NAME	DATE	PHONE #

SITE NAME:

- TAG(NUM)BER ►

INST# 19-0844250-00 ABAN# XX-XXXXXXXXXXXX PROJECT ID# 19-61713 15 CHARLOTTE DR, ANDOVER


ANDOVER, ESSEX

DRAWING TITLE:

ENVIRONMENTAL NARRATIVE

DRAWING NO:

ENV-1



MATERIAL INFORMATION

(TO BE COMPLETED DURING CONSTRUCTION)

						FITTING INSTA				
FITTING	TYPE	SIZE (IN)	STORES ITEM NUMBER (PO NUMBER IF NON-STOCK)	MATERIAL (MDPE, HDPE, STEEL)	JOINT TYPE	MANUFACTURER	LOT NUMBER	LOCATION 1	LOCATION 2	COMMENTS

						VALVE INSTAL	LATION DATA					
VALVE	TYPE	SIZE (IN)	STORES ITEM NUMBER (PO NUMBER IF NON-STOCK)	MATERIAL (MDPE, HDPE, STEEL)	MANUFACTURER	CLOCKWISE TO CLOSE?	TURNS TO CLOSE	PRESSURE RATING	DEPTH TO NUT	LOCATION 1	LOCATION 2	COMMENTS
						Y or N						

				PIPELIN	E INSTALLATION DATA		
PIPE SEGMENT	SIZE (IN)	MATERIAL (MDPE, HDPE, STEEL)	STORES ITEM NUMBER (PO NUMBER IF NON-STOCK)	MANUFACTURER	PIPE DATA PLASTIC - SDR/STRAIGHT OR COIL STEEL - WALL/GRADE/SEAM TYPE/COATING	LOCATION	COMMENTS

FITTING LEGEND

<u> </u>		
CONTROLLABLE FITTINGS		
FITTING TYPE	LABEL	SYMBOL
BOTTOM OUT MUELLER FITTING	4" MF-BO	<u> </u>
HIGH VOLUME TEE	4x2 HVT	0
SHORTSTOPP	4" SS	¤
FULL ENCIRCLEMENT SHORTSTOPP	4" SS-FE	Ø
FULL ENCIRCLEMENT SHORTSTOPP TEE	4" SST-FE	0
SIDE OUT MUELLER FITTING	4" MF-SO	¤
SPHERICAL TEE	4" SPH	0
MUELLER STOPPER	4" MF-ST	¤
SHORTSTOPP TEE	4" SST	0

NONCONTROLLABLE FITTINGS

FITTING TYPE	LABEL	SYMBOL
BLOW-DOWN	BLOW-DOWN	N/A ^
BLOW-OFF	BLOW-OFF	N/A ^
CHECK VALVE	4" CHECK VALVE	\otimes
COUPLING	4" COUPLING	1
ELL	4" 90° ELL/45° ELL	N/A*
END CAP	4" DE CAP	1
LAUNCHER-RECEIVER	LAUNCHER-RECEIVER	N/A ^
PUMPKIN	PUMPKIN	1
REDUCER	4x2 REDUCER	◀
RELIEF	RELIEF	N/A ^
SADDLE	8x4 BRANCH SADDLE	N/A*
TEE	4" INLINE TEE	N/A*
TRANSITION	4" TRANSITION	1
WELD INSULATOR	4" WELD INSULATOR	1
RISER	4" PMMP-R/CSMP-R	Ð

 - "FITTING" TO BE REPRESENTED WITH DETAILED SKETCH OF FACILITY
 * - FITTING INDICATED BY CHANGE IN DIRECTION (ELBOW) OR INTERSECTION OF FACILITIES (INLINE TEE, BRANCH SADDLE)





PROPOSED

	REVISIONS								
0	7/11/19	INITIAL / PERMIT ISSUE							
REV. #	DATE	DESCRIPTION							

ı		NAME	DATE	PHONE #
	AS-BUILT BY	X	X	Х
ı	CHECK'D BY	Х	X	Χ
ı	DRAWN BY	K MURRAY	6/17/19	978-802-5728
ı	DESIGNED BY	K MURRAY	6/17/19	978-802-5728

SITE NAME

INST# 19-0844250-00 ABAN# XX-XXXXXXXXXX PROJECT ID# 19-61713

15 CHARLOTTE DR, ANDOVER ANDOVER, ESSEX

DRAWING TITLE:

MATERIAL INFORMATION

DRAWING NO:

L-1 M

		DETAILS	RUCTION	CONST			
M Source '							
811							
Know what's below. Call before you dig.							
PROPOSED							
REVISIONS							
0 7/11/19 INITIAL / PERMIT ISSUE REV. # DATE DESCRIPTION DESIGNED BY K MURRAY 6/17/19 978-802-572 DRAWN BY K MURRAY 6/17/19 978-802-572 CHECK'D BY X X X							
AS-BUILT BY X X X NAME DATE PHONE #							
INST# 19-0844250-00 ABAN# XX-XXXXXXXXX-XX PROJECT ID# 19-61713 15 CHARLOTTE DR, ANDOVER ANDOVER, ESSEX							
DRAWING TITLE: CONSTRUCTION							
CONSTRUCTION DETAILS DRAWING NO:							
D-1							

Columbia Gas – Charlotte Drive Motion

I move that the Board approve, subject to the review and approval of the Andover Department of Public Works Engineering Division and Andover Fire Rescue, the petition of Columbia Gas requesting the permission to excavate for the purpose of replacing and/or extending its gas mains, according to blueprints provided in the petition, and to make necessary house connections along said extensions, on Charlotte Drive.

Moved by		 	-
Seconded by		 	_
Voted	to		



TOWN OF ANDOVER

Town Clerk's Office

36 Bartlet Street Andover, MA 01810 978-623-8255 townclerk@andoverma.gov

NOTICE

You are hereby notified that the Public Hearing will be held by the Andover Select Board on Tuesday, September 10, 2019 has been continued to Tuesday, September 24, 2019 in the 3rd Floor Conference Room, Town Officers, 36 Bartlet Street, at 8 p.m.

Columbia Gas of Massachusetts requests permission to excavate for the purpose of replacing and/ or extending its gas mains, according to blueprints annexed and made a part of its petition, and to make the necessary house connections along said extensions, as follows:

- To excavate approximately 2800 feet on High Plain Road from Beacon to 79 High Plain Road and 1000 feet on Virginia Road and Shirley Road, for the purpose of replacing the Cast Iron/Bare Steel-low pressure gas main with Plastic-high pressure in order to retire the Andover low pressure system. All existing gas services within the project scope will be tied into the new Plastic-high pressure main.
- As part of this project, the low pressure gas regulator vault across from 185 Lowell Street and redundant gas main on Beacon Street (390' of 6" ST-LP) and Lowell Street (665' of 6" CI-LP) will be retied.

JO#: 19-0844295-00

Should you have any concerns about this proposal, please contact Veena Kothapalli at 978-314-8061 prior to the above-mentioned Select Board's hearing date. A representative of the company will be available at 6:45 P.M. on the above date to answer any other questions you may have relating to the proposed work.

Plan(s) of the proposed work can be found on the Town of Andover website at www.andoverma.gov in the Open Meeting Calendar by searching under the public hearing date.

By order of the Select Board

Austin Simko

Town Clerk

JO#: 19-0844295-00

Date: September 13, 2019



INSTALLATION ORDER NUMBER 19-0844295-00 ABANDONMENT ORDER NUMBER 19-0844296-00 PROJECT ID 19-62826 HIGH PLAIN RD.

JOB TYPE: REPLACEMENT (557/558)

PROJECT INFORMATION

MAP/GRID NUMBER

80001004/800010019

1-800-525-8222

FIELD ENGINEER/TECHNICIAN:

CONSTRUCTION FLL:

J. ANGELARI/K. WELLS

PERMITS:

TOWN OF ANDOVER

TCC/LOA:

COUNTY:

ESSEX

TAX DISTRICT/TOWNSHIP ID:


401

MAP/GRID NUMBER:

SYSTEM NUMBER(S):

24 HR. EMERGENCY LINE:

VICINITY MAP



PROJECT DESCRIPTION

THIS PROJECT IS TO REPLACE 3,125' OF 4"/6" ST-LP ON HIGH PLAIN RD, VIRGINIA RD, AND SHIRLEY RD WITH 3,800' OF 2"/4" PH-HP AND RETIRE THE REDUNDANT MAIN ON BEACON ST (390' OF 6" ST-LP) AND LOWELL ST (665' OF 6" CI-LP). AS PART OF THIS PROJECT, THE LOW PRESSURE REGULATOR STATION- LOWELL STREET, ANDOVER WILL ALSO BE RETIRED.

SHEET INDEX

DWG.	DESCRIPTION
T-1	TITLE SHEET
GN-1	GENERAL NOTES
ENV-1	ENVIRONMENTAL PLAN NARRATIVE
O-1	OVERVIEW SHEET
L-1 - L-4	LAYOUT PLANS
D-1	CONSTRUCTION DETAILS

PROJECT SUMMARY TABLE

PRC	POSED INSTA	LLATION	PROPOSED ABANDONMENT				
LENGTH (FT)	SIZE (IN)	TYPE		LENGTH (FT)		SIZE (IN)	TYPE
2,800'	4"	PHHP		655'		6"	CILP
1,000'	2"	PHHP		390'		6"	STLP
				2,125'		6"	STLP
				1,000'		4"	STLP
3,800'	TOTAL IN	STALLATION (FEET))	4,170'		TOTAL ABANDONMENT (FEET)	
		PROPOSEI	D G	AS SERV	/ICE	S	
	F	REPLACEMENTS	T	TIE OVERS TO		TAL SERVICES	METER OUTS
ESTIMATED GAS S	SERVICES	20		8		28	28







09/24/2019

PROPOSED

REVISIONS								
0								
REV. #	DATE	DESCRIPTION						

NO-DOILT DI	NAMF	DATE	PHONF #
AS-BUILT BY	Υ	Х	Υ
CHECK'D BY	Х	Х	Х
DRAWN BY	V. KOTHAPALLI	7/9/19	978-314-8061
DESIGNED BY	V. KOTHAPALLI	7/9/19	978-314-8061

SITE NAME:

INST# 19-0844295-00 ABAN# 19-0844296-00 PROJECT ID# 19-62826 HIGH PLAIN RD. ANDOVER, ESSEX COUNTY

DRAWING TITLE:

TITLE SHEET

DRAWING NO:

T₋1

General Notes

- 1. The proposed gas main shown is approximate and is subject to change.
- 2. Property lines, structures, street lines, etc. were compiled using the NiSource GIS and are to be considered approximate.
- 3. Existing utilities, where shown, have been compiled from above ground evidence only and are to be considered approximate. NiSource does not guarantee the location of the underground utilities shown or that all existing utilities and/or subsurface structures are shown.
- 4. This project will adhere to all applicable federal, state or local permitting requirements for abandonment and installation of natural gas pipelines. All Federal, State, and Local codes and standards will be adhered including, but not limited to, the following: Code of Federal Regulations (CFR)
 - 49 CFR 192 Pipeline Safety Regulations
 - 29 CFR 1910 Occupational Safety and Health Administration (OSHA)

American Society of Mechanical Engineers (ASME)

ASME B31.8 Gas Transmission and Distribution Piping Systems

- 5. All NiSource design codes and standards will be adhered to as applicable. These standards include but are not limited to the following (note state-specific designations where applicable):
 - GS 1100.010(IN, KY, MA, MD, OH, PA, VA) Locating Gas Facilities
 - GS 1100.040(MA and VA only) Damage Prevention When Using Conventional Excavation Technologies
 - GS 1100.050(IN, OH, VA) Damage Prevention Using Trenchless Technology
 - GS 1170.010(IN) Gas Control Room Management
 - GS 1210.010(MA) Nondestructive Testing And Visual Inspection
 - GS 1300.010 Fusion And Mechanical Joining
 - GS 1301.010 Plastic Pipe Fusion And Mechanical Joining Qualification Of Personnel
 - GS 1302.010(VA) Butt Fusion Joining
 - GS 1304.010 Electrofusion Joining
 - GS 1320.010 Mechanical Coupling Connections
 - GS 1323.010 Flange Connections
 - GS 1400.010 Corrosion Control General
 - GS 1410.010(VA) Metallic Pipeline Exposures
 - GS 1420.035 Coating Repair Methods For Mill Applied Coatings
 - GS 1420.040 Coating Methods For Girth Welds, Fittings, Risers & Other Below Grade Appurtenances
 - GS 1420.410 Corrosion Control Inspection Of Steel Pipe Coating
 - GS 1420.510 Installation Of Galvanic Anodes
 - GS 1420.520 Installation Of Test Stations GS 1430.320 Ultrasonic Thickness Gauge
 - GS 1500.010(MA, OH) Pressure Testing

 - GS 1670.020(IN, KY, MA, MD) Odor Level Monitoring GS 1670.040 Pipeline Conditioning New Pipelines
 - GS 1680.010 Tie-Ins And Tapping Pressurized Pipelines
 - GS 1680.020 Plastic To Steel Transition Connections
 - GS 1680.040 Squeeze Off Procedure For Plastic Pipe
 - GS 1680.050 Squeeze Off Guidelines For Steel Pipe
 - GS 1690.010 Purging
 - GS 1708.020(IN, KY, MA, MD, PA) Leakage Surveys
 - GS 1740.010(MA, OH, PA, VA) Abandonment Of Facilities
 - GS 1740.012(MA, PA) Abandoning Facilities Service Tee Removal
 - GS 1742.010(VA) Discontinuing Gas Service
 - GS 1754.010(KY, OH) Operation And Maintenance Of Pressure Gauges
 - GS 1770.010 Prevention Of Accidental Ignition
 - GS 1782.010(MA) Protecting Cast Iron Pipelines
 - GS 3000.020(VA) Inspection Of Materials GS 3000.900 Work Site Restoration
 - GS 3010.030 Bends And Elbows
 - GS 3010.050(IN, MA) Installation Of Pipe In A Ditch

 - GS 3010.060(IN) Installation Of Plastic Pipe
 - GS 3010.080(MA, OH, VA) Underground Clearance
 - GS 3010.090(IN, MA, PA, VA) Cover
 - GS 3010.100(VA) Transmission Lines And Distribution Mains Trenchless Technology
 - GS 3010.102(VA) Directional Boring
 - GS 3010.210(MA only) Use Of End Caps On Steel Pipe GS 3020.030 Service Line Connections To Main Piping
 - HSE 4100.010 Hazardous Atmosphere Considerations
 - HSE 4100.020 Work Zone Traffic Protection HSE 4100.040 Excavation (Trenching) Safety
 - HSE 4120.010 Welding And Cutting
 - HSE 4200.020 Protective Footwear
 - HSE 4200.030 Eye And Face Protection
 - HSE 4200.040 Hand Protection
 - HSE 4200.050 Head Protection
 - HSE 4440.030(KY, MA, MD, OH, PA, VA) Spoil Handling During Excavations
 - ON 18-09 Additional Requirements For Tie-Ins Involving Low Pressure Facilities
 - WM Columbia Gas Welding Manual

- 6. Prior to beginning any excavation on site, the person responsible for earth moving shall notify utility owners of their intent to excavate and to have the exact locations of the utility lines marked by contacting the one call center in their state subject to any applicable state advance notification requirements.
- 7. Proposed or completed gas facility installation location references may be indicated by a combination of the following codes:

F - FRONT BK - BACK L - LEFT R - RIGHT B - BUILDING EDGE

CLP - CENTER OF PAVEMENT CLR - CENTER OF RIGHT-OF-WAY

CEL - CENTER OF EASTBOUND LANE CWL - CENTER OF WESTBOUND LANE CNL - CENTER OF NORTHBOUND LANE

CSL - CENTER OF SOUTHBOUND LANE

CU - CURB

D - DRIVEWAY EDGE

EP - EDGE OF PAVEMENT ES - EDGE OF SIDEWALK

PL - PROPERTY LINE

DRAWING LEGEND

Gas Main Sym	bology
	Existing Gas Main
	Existing Gas Main to Be Abandoned
	Proposed Gas Main
Cas Main Mate	Proposed Gas Main Uprate
CS	erial/Pressure Label References Coated Steel Gas Main
CI	Cast Iron Gas Main
BS	Bare Steel Gas Main
WI	Wrought Iron Gas Main
PH	High Density Polyethylene Gas Main
PM	Medium Density Polyethylene Gas Mair
LP	Low Pressure
IP	Intermediate Pressure
MP	Medium Pressure
HP	High Pressure
	allation Method Label References
AT BH	Attached Bridge Hanger
BLGH	Bridge Hanger Building Hanger
DB	Directional Bore
IS	Inserted
OC	Open Cut
PB	Pneumatic Bore
PL	Plowed
RT	Roof Top
(E)	Existing
(P)	Proposed
— (W1)	Weld Location
— (T1)	Gas Main Tie-in Location
—(A1)	Gas Main Abandonment Location
\ /	

Gas Facility Symbology Gas Valve (Gate - GV, Plug - PV, PE Ball - BP, ST Ball - BV) Critical Gas Valve High Volume Tapping Tee ○2"HVTT Pressure Control Fitting - ShortStopp Tee ○2"SST Pressure Control Fitting - Spherical Tee ○4"SPH Pressure Control Fitting - Mueller Bottom-out ○ 6"MF-BO Pressure Control Fitting - Mueller Side-out ○ 6"MF-SO Pressure Control Fitting - Mueller Flange Tee ○ 4"MF-FT Pressure Control Fitting - ShortStopp Pressure Control Fitting - Mueller Stopper **Transition** End Cap Riser Reducer Electronic Marker Flush-mounted Tracer Wire Station Post Pipeline Marker with Tracer Wire Gas Main Marker without Tracer Wire Test Well Regulator Station Single Customer Regulator Meter with Regulator Test Point (Station) Gas Service Tie-over Gas Service Replacement Meter Move Out Swing Tie Symbology Telephone Manhole Drain Manhole **Electric Manhole** Catch Basis Sewer Manhole Fire Hydrant Utility Pole Property Marker Telephone Pedestal **Television Pedestal** Unknown Manhole Water Box Water Gate **Electric Pedestal** Iron Pin

Light Pole





09/24/2019

PROPOSED

REVISIONS										
0										
REV. #	DATE	DESCRIPTION								
	•									

	NAME	DATE	PHONE #
AS-BUILT BY	Х	Х	Х
CHECK'D BY	Х	X	Х
DRAWN BY	V. KOTHAPALLI	7/9/19	978-314-8061
DESIGNED BY	V. KOTHAPALLI	7/9/19	978-314-8061

SITE NAME:

INST# 19-0844295-00 ABAN# 19-0844296-00 PROJECT ID# 19-62826 HIGH PLAIN RD.

ANDOVER, ESSEX COUNTY

DRAWING TITLE:

GENERAL NOTES

DRAWING NO:

GN-1

Environmental Plan Narrative

- 1. There is no Site-Specific Erosion Control plan requirement for this project. This plan narrative, with the project Environmental Compliance Plan (ECP), provide information regarding all environmental requirements. All NiSource construction activities must be performed in accordance with the NiSource Environmental Construction Standards (ECS) and the project ECP.
- 2. The project ECP must be reviewed with construction and contractor personnel prior to the start of construction activities. This includes any tree clearing activities required prior to the start of pipeline construction.
- 3. All NiSource construction projects must have a clearly defined work area or limits of disturbance (LOD). The LOD includes the permitted project area and any additional work space needed for laydown yards, soil stockpiling areas, access routes, etc. Notify NRP of any additional work space that may be needed outside of what is shown on this job order sketch.

Description and Minimum Requirements for Erosion and Sediment Control Measures

The information provided below outlines the purpose of common measures and how and when they shall be applied to the site. Figures showing installation details are provided in the NiSource ECS manual.

Perimeter Barriers: Perimeter barriers, such as silt fence and compost filter sock may be installed along the outside of the project area or around sensitive areas to slow and filter sediment laden runoff before it leaves the work area.

These measures are required in the following areas:

- 1. When work is occurring adjacent to streams, wetlands or other sensitive areas.
- Around HDD bore pits adjacent to streams, wetlands or other sensitive areas.
- 3. Around soil stockpiles that will remain uncovered for greater than one working day.
- 4. Where any work areas or excavations will remain disturbed (unstabilized) for longer than one working day.

Inlet Protection: Storm drain inlet protection, both curb and drop inlets, are required in active work areas where there is functioning storm sewer to slow and filter water draining into the system. In areas where the work area is adjacent to, or water from the site flows onto a paved roadway, inlet protection will be placed in all functioning outlets.

Check dams: Rock check dams may be installed in areas of concentrated flow in a ditch line to slow runoff and allow sediment to settle prior to discharge. Check dams may also be used as a break in a perimeter barriers where runoff is concentrated and perimeter barriers are insufficient to detain runoff. Check dams are required when working in ditch lines where work will remain active for more than 1 day and as a supplementary measure determined to be needed during construction.

Dewatering Devices: A filter bag, or other approved dewatering device, must be used during all dewatering activities to remove suspended sediment from the water prior to discharge into the environment. Dewatering devices must be used in areas including, but not limited, to trench or pit dewatering and treatment of excess HDD mud.

Construction Entrances: In cases where vehicular access from the work area occurs at a single point for multiple days, a rock construction entrance must be installed. A stabilized construction entrance may not be feasible during construction within or immediately adjacent to a roadway as the construction project moves linearly along the road. In these cases, care should be taken to minimize vehicular access and the roadway shall be regularly cleaned of tracked sediment throughout the work day. Alternatives to rock entrances include the placement of timber mats or similar non erodible materials. Use of these alternatives must be approved by the NRP group or environmental inspector.

Trench Plugs/Breakers: Trench breakers consist of sand or earth filled sacks placed at intervals along the pipeline trench. Trench breakers may be installed at intervals within the trench to reduce water velocity along the pipeline bedding that can result in erosion during construction and after backfilling. Trench plugs consist of clay, bentonite or other impermeable material and are required adjacent to stream and wetland crossings to ensure that the flow of water along the trench line does not impact the waterbody.

Temporary Stabilization: Temporary stabilization includes the placement of an annual or cover crop and a straw or other mulch covering to protect disturbed areas from precipitation. In certain cases where redisturbance will occur prior to a normal germination period, temporary stabilization with mulch or other covering may be completed without the application of seed.

Temporary stabilization will be completed on the following areas to reduce erosion from bare ground during rainfall events:

- 1. Any areas, including stockpiles or tie-in pits, which will remain open overnight without perimeter controls.
- 2. Any work area that will remain bare/disturbed longer than 7 days (4 in PA) without being actively worked within that time. Seeding must be completed within this time window.

Permanent Stabilization: Includes the placement of a permanent seed mix and a straw or other mulch covering to permanently stabilize the disturbed areas. Proper ground/ seed bed preparation (e.g. topsoiling, raking, decompaction) shall be completed as appropriate to the existing site area to provide a sufficient surface for seed germination.

Permanent seeding shall be completed immediately after work completion in all work areas without structural controls; regardless of whether the surrounding area is vegetated. Permanent seeding shall be applied within 7 days (4 days in PA) of work completion in areas all other areas; with the exception of work area protected by adequate structural controls where the surrounding area is an active construction site and was not vegetated prior to the start of work.

Erosion Control Blanket/Matting: Erosion control blanket is a straw matting that can be rolled out over a disturbed area and secured using pins or stakes. This blanket may be required on steeper sloped areas to hold seed and mulch in place. Erosion control blanket can also be useful in protecting the seed and holding moisture in dry, windy areas. Erosion control blanket must be used in restoration adjacent to streams or wetlands. It should also be used in areas with high erosion potential (e.g. steep slopes, embankments, ditch lines).

Maintenance: The job site shall be inspected by construction personnel at the end of each day to ensure that any controls are functioning and that the work area is sufficiently contained. Required maintenance of NiSource installed controls or corrective actions shall be performed immediately or within the time frames noted by an Environmental Inspector.

Measures previously installed by third parties shall be maintained by NiSource under the following circumstances:

- 1. The control is not properly functioning and is being used to contain sediment and prevent erosion immediately adjacent to NiSource work.
 - Damage to the control is the result of work performed by NiSource.

Projects Within Third Party Construction Sites:

In situations where NiSource projects are being completed within a larger project or development area, NiSource is still responsible for ensuring our work is in compliance with all laws and regulations. This must be documented under one of the following scenarios:

- 1. Prior to the start of construction activities, a qualified NiSource representative will verify that all NiSource work activities will be covered under the third party's approved site plan and/or SWPPP and that the appropriate EC measures are installed and functioning. This review will be documented and retained in the project records.
- 2. If the EC measures required by the third party's approved site plan are not present or functioning, NiSource construction activities may commence under the following conditions:
- a. All disturbed NiSource work areas are stabilized at the end of the work day.
- b. Any NiSource work areas requiring disturbance over one working day (e.g. stockpiles, tie-in pits) will require perimeter controls or temporary mulching or covering on a daily basis.
- c. The overall project SWPPP is present/available and all NiSource activities remain within compliance of all outlined requirements.
- d. Any additional permits required for the NiSource work are obtained.
- e. The third party permit holder is informed of the site deficiencies and NiSource's plan to complete the work.

Final stabilization measures shall be completed as described in the applicable Temporary or Permanent Stabilization sections above to match the adjacent conditions of the third party project.

In addition to the preceding methods, the following erosion control measures will be used on a daily basis regardless of whether the work area is inside third party controls:

- Perimeter barriers around bore pits at wetland/ stream bores
- Dewatering activities using a filter bag or other approved method
- Roadway cleaning daily for sediment tracked onto paved surfaces


Wetland and Stream Crossings, Sensitive Areas:

All wetlands, stream crossings and other sensitive areas (e.g. managed lands, parks, and endangered species habitat areas) must be marked in the field with caution flagging prior to the start of clearing activities and/or land disturbing activities.

Any requirements for construction within these areas will be outlined within the ECP and the attached permit documents. These permits must also be reviewed prior to the start of construction.

ENVIRONMENTAL EROSION AND SEDIMENT CONTROL SYMBOLOGY

ENVIRONMENTAL EROSION CONTROL BLOCKS (on Env-ErosionControl layer)







09/24/2019

PROPOSED

		REVISIONS							
0									
REV.#	DATE	DESCRIPTION							

DESIGNED BY	V. KOTHAPALLI	7/9/19	978-314-8061
DRAWN BY	V. KOTHAPALLI	7/9/19	978-314-8061
CHECK'D BY	X	Х	Х
AS-BUILT BY	Х	Х	Х
	NAME	DATE	PHONE #

SITE NAME:

- TAG(NUM)BER ►

______ 24′′ **____**__

_____ TP ____

.~~~~~~~

_____ LOD _____


INST# 19-0844295-00 ABAN# 19-0844296-00 PROJECT ID# 19-62826 HIGH PLAIN RD. ANDOVER, ESSEX COUNTY

DRAWING TITLE:

ENVIRONMENTAL NARRATIVE

DRAWING NO:

ENV-1









Know what's below.

Call before you dig.



09/24/2019



REVISIONS								
0								

DESIGNED BY	V. KOTHAPALLI	7/9/19	978-314-8061
DRAWN BY	V. KOTHAPALLI	7/9/19	978-314-8061
CHECK'D BY	Х	Х	Х
AS-BUILT BY	Х	Х	Х
	NAME	DATE	PHONF #

DESCRIPTION

SITE NAME:


REV. # DATE


INST# 19-0844295-00 ABAN# 19-0844296-00 PROJECT ID# 19-62826 HIGH PLAIN RD. ANDOVER, ESSEX COUNTY

DRAWING TITLE:

OVERVIEW SHEET

DRAWING NO:









	AS-BUILT NOTES (TO BE COMPLETED DURING CONSTRUCTION)											
N'Source 1												
PROPOSED												
REVISIONS												
REV. # DATE DESCRIPTION												
DESIGNED BY V. KOTHAPALLI 7/9/19 978-314-0 DRAWN BY V. KOTHAPALLI 7/9/19 978-314-0 CHECK'D BY X X X AS-BUILT BY X X X												
NAME DATE PHONE SITE NAME:												
INST# 19-0844295-00 ABAN# 19-0844296-00 PROJECT ID# 19-62826												
HIGH PLAIN RD. ANDOVER, ESSEX COUNTY												
DRAWING TITLE:												
CONSTRUCTION DETAILS												
DRAWING NO:												
D-1												

Columbia Gas – High Plain Road Motion

I move that the Board approve, subject to the review and approval of Andover Department of Public Works Engineering Division and Andover Fire Rescue, the petition of Columbia Gas requesting the permission to excavate for the purpose of replacing and/or extending its gas mains, according to blueprints provided in the petition, and to make necessary house connections along said extensions, on approximately 2800 feet on High Plain Road from Beacon to 79 High Plain Road and 1,000 feet on Virginia Road and Shirley Road.

Moved by		 	
Seconded by		 	
Voted	to		